

PRINT DATA SETUP

Settings for Bellutti Planen Production

10/2018

Measurements	All files have to be created in proportional scale 1:1 or 1:10.
Resolution	PVC Banners, Mesh & Flags 120 DPI in scale 1:1 Foils, Paper 200 DPI in scale 1:1 Board 200 DPI in scale 1:1 If you work in scaled dimensions, keep in mind: 1:1 – 75 DPI → 1:10 – 750 DPI Recommendation: The larger the final format the more important is a higher resolution.
Colour Management	All our productions and machines use 4 colour mode CMYK. Any spot colour like HKS, RAL or Pantone can only be displayed and produced within the CMYK Colour Space. If you intend to use spot colour, please advise your contact at Bellutti Planen accordingly.

PLEASE NOTE **Any fonts used within your print files (even embedded fonts within Logos & Claims) have to be converted into paths or have to be embedded in the files. If open files are delivered, you have to deliver used pictures, logos & fonts with the files separately.**

White & Cut/Outline	If you intend to place an order with additional prints in white colour or containing contour cuts please use separate colour channels created with spot colours. In order to guarantee perfect settings and productions the colour channel for white colour print has to be named "white" and the channel for contour cuts has to be named "cutline". Both channels have to be set to "overprint". The colour for the channels can be chosen freely. For these options PDF 1.7 setting is mandatory!
Preview/Proof	In order to be able to adapt final colours to our machines please send a binding Proof and/or colour definition for CMYK values.

Optimization Ideally you submit print files using "Print Settings PDF 1.7" with a minimum bleed of 10mm. If print files are submitted with other settings and parameters, additional costs can occur.
In order to optimize and facilitate our partnership and to save time we have created Pre-Settings for you. We created two different PDF setting versions, which are available for free download and will be described in this document. All relevant downloads and installation guides can be found on our website: <http://www.plakativ-werbettechnik.at/service/technische-downloads.html>
Additionally, you will also find a colour management ICC Profile: ISOcoated_v2.

Open Files If you deliver open files, additional costs may occur. In order to set up print files out of open files it is mandatory to submit screenshots or preview PDFs of your print files. We are able to import/open/use the following file formats:
Adobe CS6, Image file type (Note DPI/scale ratio) JPEG, TIFF, PNG, PDF

File Transfer	Per Mail: Data up to 10 MB More than 10 MB Filesharing websites like WeTransfer File transfer activated for Firefox, Safari, Chrome and I Explorer. Per Medium: CD, DVD, USB Stick, FireWire HDD, USB HDD
----------------------	---

If print files are submitted with other settings and parameters, additional costs and delay in delivery will occur.

For any questions please contact our graphic department - +43 (0)512/264150 Ext. 20